

ProClassic®**Interior Waterbased Acrylic-Alkyd Satin**

(US)B33W01851 Extra White, (Canada) B33WQ1851 Extra White

**SHERWIN
WILLIAMS®****CHARACTERISTICS**

ProClassic® Interior Waterbased Acrylic-Alkyd Satin is a high-quality product, with excellent flow and leveling characteristics for a smooth and durable finish.

Project Uses :

Trim areas and Molding
Cabinets, Doors, Windows
Kitchens, Baths
Laundry rooms
High Traffic areas

Use On :

Drywall-Plaster
Paneling – Wood
Metal
Concrete-Masonry

Color:

Most Colors

To optimize hide and color development, always use the recommended P-Shade primer.

Coverage:

350-400 sq. ft. per gallon
@ 4 mils wet, 1.4 mils dry

Drying Time, @ 77°F, 50% RH :

Tack Free: 20-40 minutes
Touch: 1-2 Hour
Recoat: 4 Hours
Drying and recoat times are temperature, humidity, and film thickness dependent.

Finish:

27-37 units @ 60°

Tinting with CCE only :

Base : **oz. per gallon :** **Strength :**

Extra White 0-7 SherColor

Extra White B33W01851

(may vary by color)

V.O.C.(less exempt solvents):

less than 50 grams per litre; 0.42 lbs. per gallon
As per 40 CFR 59.406

Volume Solids: 34 ±2%

Weight Solids: 48 ±2%

Weight per Gallon: 10.36 lbs

Flash Point: greater than 200°F PMCC

Vehicle Type: Acrylic-Alkyd Hybrid

Shelf Life: 36 months, unopened

Flame Spread: Class A

COMPLIANCE

As of 06/19/2026, Complies with :

OTC	Yes
OTC Phase II	Yes
S.C.A.Q.M.D.	Yes
CARB	Yes
CARB SCM 2007	Yes
CARB SCM 2020	Yes
Canada	Yes
LEED® v4 & v4.1 Emissions	No
LEED® v4 & v4.1 V.O.C.	Yes
EPD-NSF® Certified	No
MIR-Manufacturer Inventory	No
MPI®	#168

APPLICATION

Apply at temperatures above 50°F.
No reduction needed.

Brush :

Use a nylon-polyester brush such as Purdy® XL®. Do not use China bristle brush.

Roller :

Use a high-quality 1/4- 3/4 inch nap woven roller cover such as Purdy® White Dove™.

For specific brushes and rollers, please refer to our Brush and Roller Guide.

Spray – Airless :

Pressure 2000 p.s.i.
Tip (fine finish) .010-.014 inch
(A fine finish tip is the preferred method of spray application due to the characteristics of this product. You can spray with tips from .013 to .017 inch; however, you should test the application on the particular item being painted.)

APPLICATION TIPS

Make sure product is completely agitated (mechanically or manually) before use.

SPECIFICATIONS**Block :**

1 coat Loxon Acrylic Block Surfacer
2 coats ProClassic Waterbased Acrylic-Alkyd

Drywall :

1 coat Premium Wall & Wood Primer
2 coats ProClassic Waterbased Acrylic-Alkyd

Masonry :

1 coat Loxon Acrylic Block Surfacer
2 coats ProClassic Waterbased Acrylic-Alkyd

Plaster :

1 coat Loxon Concrete & Masonry Primer
2 coats ProClassic Waterbased Acrylic-Alkyd

Wood :

1 coat Premium Wall & Wood Primer
2 coats ProClassic Waterbased Acrylic-Alkyd

Other primers may be appropriate.

When repainting involves a drastic color change, or coating over heavily stained areas, a coat of primer will improve the hiding performance of the topcoat color.

ProClassic®

Interior Waterbased Acrylic-Alkyd Satin

SURFACE PREPARATION

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a **HEPA** vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Existing peeled or checked paint should be scraped and sanded to a sound surface. Glossy surfaces should be sanded dull. Stains from water, smoke, ink, pencil, grease, etc. should be sealed with the appropriate primer-sealer. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of the system.

Caulking :

Gaps between walls, ceilings, crown moldings, and other interior trim can be filled with the appropriate caulk after priming the surface.

Drywall :

Fill cracks and holes with patching paste-spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.

Masonry, Concrete, Cement, Block :

All new surfaces must be cured according to the supplier's recommendations – usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Concrete & Masonry Primer.

SURFACE PREPARATION

Mildew :

Clean mildew from the Surface: Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.

Plaster :

Bare plaster must be cured and hard. Textured, soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon of clean water. Repeat until the surface is hard, rinse with clean water and allow to dry.

Wood :

Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.

CAUTIONS

Can be used for exterior doors, trim, and other small areas of wood or metal. Do not use on the main body of exterior structures.

Non-Photochemically reactive.

Before using, carefully read **CAUTIONS** on label.

CRYSTALLINE SILICA Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

HOTW 06/19/2026 B33W01851 19 40
FRC,SP

CLEANUP INFORMATION

Clean spills, spatters, hands and tools immediately after use with soap and warm clean water. After cleaning, flush spray equipment with compliant cleanup solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents. Do not pour unused contents down the drain. Consult with local authorities for method of disposal and recycling.